

SAFETY DATA SHEET

1. Identification

Product identifier TC303 Aluminum Brightener

Other means of identification

Product Code 1130

Recommended use Automotive Detailing

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company nameMalco Products, Inc.Address361 Fairview AveBarberton, OH 44203

United States

 Telephone
 Phone
 800-253-2526

 Fax
 330-753-2025

Website www.malcopro.com
E-mail msdsinfo@malcopro.com
Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 1

Acute toxicity, dermal

Acute toxicity, inhalation

Category 4

Skin corrosion/irritation

Category 1

Serious eye damage/eye irritation

Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements







Signal word Danger

Hazard statement Fatal if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage.

Harmful if inhaled.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce

vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Take off contaminated clothing and wash before reuse. Overexposure may produce hypocalcemia, therefore systemic

administration of calcium gluconate may be necessary

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: TC303 Aluminum Brightener

Version #: 04 Revision date: 01-27-2021 Issue date: 06-25-2015

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

% of the mixture consists of component(s) of unknown acute inhalation toxicity. 36.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 36.5% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

hemical name Common name and synonyms		CAS number	%	
Ethylene Glycol Monobutyl Ether		111-76-2	20 - < 30	
Citric Acid Anhydrous		77-92-9	5 - < 10	
Hydrogen Fluoride		7664-39-3	5 - < 10	
Orthophosphoric Acid		7664-38-2	5 - < 10	
Other components below reportable	levels		60 - < 70	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contactTake off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse. Overexposure may produce hypocalcemia, therefore systemic

administration of calcium gluconate may be necessary

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

medical attention and special treatment needed

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an

immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General informationIf you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Ingestion

Alcohol resistant foam. Powder.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards
No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: TC303 Aluminum Brightener

SDS US

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Should not be released into the environment.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Orthophosphoric Acid (CAS 7664-38-2)	PEL	1 mg/m3	
US. OSHA Table Z-2 (29 CFR 1910.	1000)		
Components	Туре	Value	
Hydrogen Fluoride (CAS 7664-39-3)	TWA	3 ppm	
US. ACGIH Threshold Limit Values	•		
Components	Туре	Value	
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	TWA	20 ppm	
Hydrogen Fluoride (CAS 7664-39-3)	Ceiling	2 ppm	
	TWA	0.5 ppm	
Orthophosphoric Acid (CAS 7664-38-2)	STEL	3 mg/m3	
	TWA	1 mg/m3	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Hydrogen Fluoride (CAS 7664-39-3)	Ceiling	5 mg/m3	
		6 ppm	
	TWA	2.5 mg/m3	
		3 ppm	
Orthophosphoric Acid (CAS 7664-38-2)	STEL	3 mg/m3	
,	TWA	1 mg/m3	

Biological limit values

ACGIH Biological	Exposure	Indices
-------------------------	-----------------	---------

Components	Value	Determinant	Specimen	Sampling Time
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin. Hydrogen Fluoride (CAS 7664-39-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Hydrogen Fluoride (CAS 7664-39-3) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

controls

Wear appropriate chemical resistant gloves. Hand protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Chemical respirator with organic vapor cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash considerations

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear. Liquid. Physical state **Form** Liquid. Color Red-orange Odor Acidic

Odor threshold Not available.

1 - 2

Melting point/freezing point Not available. Initial boiling point and boiling range

Not available.

Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits Not available. **Explosive limit - lower (%)**

Explosive limit - upper (%) Not available. Vapor pressure Not available. Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive. Not oxidizing. Oxidizing properties

1.09 Specific gravity

10. Stability and reactivity

Reactivity Reacts violently with strong alkaline substances. This product may react with reducing agents.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not mix with

other chemicals.

Bases. Strong oxidizing agents. Reducing agents. Incompatible materials **Hazardous decomposition**

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Harmful if inhaled. Inhalation

Causes severe skin burns. Harmful in contact with skin. Skin contact

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye damage.

Fatal if swallowed. Causes digestive tract burns. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. May cause respiratory irritation.

Information on toxicological effects

In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and **Acute toxicity**

central nervous system effects. Fatal if swallowed. Harmful if inhaled. Harmful in contact with skin.

Components **Species Test Results**

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Acute Dermal

LD50 Rabbit 400 mg/kg

Oral

LD50 560 mg/kg Rat

Orthophosphoric Acid (CAS 7664-38-2)

Acute Dermal

> LD50 Rabbit 2740 mg/kg

Oral

LD50 1530 mg/kg Rat

Material name: TC303 Aluminum Brightener

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not applicable.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

EcotoxicityBecause of the low pH of this product, it would be expected to produce significant ecotoxicity upon

exposure to aquatic organisms and aquatic systems.

Components Species Test Results

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Aquatic

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol Monobutyl Ether 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: TC303 Aluminum Brightener

SDS US

14. Transport information

DOT

UN3264 **UN** number

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrofluoric Acid) **UN proper shipping name**

Transport hazard class(es)

Class 8 **Subsidiary risk** 8, Label(s) Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B2, IB2, T11, TP2, TP27

Packaging exceptions None 202 Packaging non bulk 243 Packaging bulk

IATA

UN number UN3264

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. **UN** proper shipping name

Transport hazard class(es)

Class 8 **Subsidiary risk** Ш Packing group **Environmental hazards** No. **ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN3264

UN proper shipping name CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. Transport hazard class(es)

Not established.

Class 8 **Subsidiary risk** Ш Packing group **Environmental hazards**

Marine pollutant No. F-A, S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



Material name: TC303 Aluminum Brightener

IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Hydrogen Fluoride (CAS 7664-39-3) Listed. Orthophosphoric Acid (CAS 7664-38-2) Listed.

SARA 304 Emergency release notification

Hydrogen Fluoride (CAS 7664-39-3) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Reportable Chemical name **CAS** number **Threshold** Threshold Threshold quantity planning quantity planning quantity, planning quantity, (pounds) (pounds) lower value upper value (pounds) (pounds)

100

Hydrogen Fluoride 7664-39-3 100

Classified hazard

Acute toxicity (any route of exposure)

categories Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.Hydrogen Fluoride7664-39-35 - < 10</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Hydrogen Fluoride (CAS 7664-39-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Hydrogen Fluoride (CAS 7664-39-3)

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Orthophosphoric Acid (CAS 7664-38-2) High priority

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

Hydrogen Fluoride (CAS 7664-39-3) Orthophosphoric Acid (CAS 7664-38-2)

Material name: TC303 Aluminum Brightener

SDS US

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No
Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand Inventory

Philippines Philippine Inventory of Chemicals and Chemical Substances

Yes

(PICCS)

TaiwanTaiwan Toxic Chemical Substances (TCS)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information, including date of preparation or last revision

 Issue date
 06-25-2015

 Revision date
 01-27-2021

Version # 04

Disclaimer Malco Products, Inc. cannot anticipate all conditions under which this information and its product,

or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any

process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: TC303 Aluminum Brightener

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).