SAFETY DATA SHEET

1. Identification

Product identifier Spray Coat Aerosol

Other means of identification

Product Code 198211 Recommended use Dressing **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Malco Products, Inc. Company name **Address** 361 Fairview Ave Barberton, OH 44203

United States

Telephone Phone 800-253-2526

330-753-2025 Fax

Website www.malcopro.com E-mail msdsinfo@malcopro.com **Contact person Technical Department**

1-800-424-9300 Phone **Emergency phone number**

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2 **Health hazards** Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2 Germ cell mutagenicity Category 1B Carcinogenicity Category 1B Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Category 2

Category 1

Aspiration hazard Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Harmful

if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated

exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face

protection.

Material name: Spray Coat Aerosol SDS US Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and

wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha (Petroleum), Hydrotreated Light		64742-49-0	30 - < 40
N-butane		106-97-8	30 - < 40
n-hexane		110-54-3	10 - < 20
Propane		74-98-6	10 - < 20
Cyclohexane		110-82-7	< 1
Other components below reportable le	evels		5 - < 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

may cause chronic effects.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Powder. Foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Durin

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose belder or massive fire particles if possible. If not withdraw and let fire burn out

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

breathe fumes.

General fire hazards Flammable aerosol.

Material name: Spray Coat Aerosol 198211 Version #: 01 Issue date: 11-05-2015

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	r Contaminants (29 CFR 1910.1000) Type	Value	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
,		300 ppm	
n-hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Value	es.		
Components	Туре	Value	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
N-butane (CAS 106-97-8)	STEL	1000 ppm	
n-hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
		300 ppm	
N-butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
n-hexane (CAS 110-54-3)	TWA	180 mg/m3	

Material name: Spray Coat Aerosol

198211 Version #: 01 Issue date: 11-05-2015 3 / 10

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
		50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

Accin Biological Exposure maloce	ACGIH	Biological	Exposure	Indices
----------------------------------	-------	-------------------	-----------------	---------

Components	Value	Determinant	Specimen	Sampling Time
n-hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-hexane (CAS 110-54-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Compressed liquefied gas.

Physical state Liquid.
Form Aerosol.

Color Clear.Colorless

Odor Solvent.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -219.24 °F (-139.58 °C) estimated Initial boiling point and boiling 8.82 °F (-12.88 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) estimated

Evaporation rateNot available.Flammability (solid, gas)Not applicable.Upper/lower flammability or explosive limits

Flammability limit - lower

1.8 % estimated

(%)

Flammability limit - upper

8.5 % estimated

(%)

Explosive limit - lower (%) Not available.

SDS US

4 / 10

198211 Version #: 01 Issue date: 11-05-2015

Explosive limit - upper (%) Not available.

Vapor pressure 3646.7 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Auto-ignition temperature 496.4 °F (258 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 0.36 g/cm3 **Explosive properties** Not explosive.

Flammability class Flammable IA estimated
Heat of combustion 35.39 kJ/g estimated
Heat of combustion (NFPA 35.39 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Percent volatile 83.69 % estimated

Specific gravity 0.66 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by

inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled. Narcotic effects.

Components Species Test Results

Cyclohexane (CAS 110-82-7)

Acute Oral

LD50 Mouse 1300 mg/kg

Rat 29820 mg/kg

198211 Version #: 01 Issue date: 11-05-2015

Components **Species Test Results**

N-butane (CAS 106-97-8)

Acute

Inhalation

LC50 Mouse 680 mg/l, 2 Hours

> Rat 658 mg/l, 4 Hours

n-hexane (CAS 110-54-3)

Acute Inhalation

LC50 Mouse

48000 ppm, 4 Hours

Oral LD50

Rat 24 mg/kg

Wistar rat 49 mg/kg

Propane (CAS 74-98-6)

Acute

Inhalation

LC50 Rat > 1442.847 mg/l, 15 Minutes

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may **Chronic effects**

be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

Cyclohexane (CAS 110-82-7)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours

SDS US 6 / 10 198211 Version #: 01 Issue date: 11-05-2015

Species Test Results Components

n-hexane (CAS 110-54-3)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Cyclohexane 3.44 2.89 N-butane 3.9 n-hexane Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name

Transport hazard class(es)

Aerosols, Flammable

2.1 Class Subsidiary risk

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

N82 Special provisions Packaging exceptions 306

IATA

UN number UN1950

Aerosols, Flammable UN proper shipping name

Transport hazard class(es)

2.1 **Class** Subsidiary risk

Packing group Not applicable.

Environmental hazards No.

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Forbidden.

Cargo aircraft only

Forbidden.

IMDG

UN number UN1950

Aerosols, Flammable UN proper shipping name

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

2.1 Class Subsidiary risk

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cyclohexane (CAS 110-82-7) Listed. n-hexane (CAS 110-54-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
n-hexane	110-54-3	10 - < 20

Material name: Spray Coat Aerosol

8 / 10 198211 Version #: 01 Issue date: 11-05-2015

Chemical name	CAS number	% by wt.	
Cyclohexane	110-82-7	< 1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0)

N-butane (CAS 106-97-8) n-hexane (CAS 110-54-3)

US. Massachusetts RTK - Substance List

Cyclohexane (CAS 110-82-7) N-butane (CAS 106-97-8) n-hexane (CAS 110-54-3) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Cyclohexane (CAS 110-82-7) N-butane (CAS 106-97-8) n-hexane (CAS 110-54-3) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexane (CAS 110-82-7) N-butane (CAS 106-97-8) n-hexane (CAS 110-54-3) Propane (CAS 74-98-6)

US. Rhode Island RTK

Cyclohexane (CAS 110-82-7) N-butane (CAS 106-97-8) n-hexane (CAS 110-54-3) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Material name: Spray Coat Aerosol SDS US 9 / 10 Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

, ,

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-05-2015

Version # 01

Disclaimer N

Malco Automotive cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: Spray Coat Aerosol sps us

198211 Version #: 01 Issue date: 11-05-2015